BFL1390 Fibre Metal Cutting Laser

boxford

A range of metal cutting fibre laser systems built to Boxford specifications. Our high precision metal cutting fibre lasers are ideally suited to all kinds of training, prototyping and low to medium volume manufacturing applications.




Materials which can be fibre laser processed:

Mild steel
Stainless steel
Aluminium
Anodised aluminium
Zintec
Galvanised steel
Brass
Shim steel
and more...

Boxford Fibre metal cutting lasers include:

- Fully enclosed system for optimal fume and debris management
- Rigid construction and motion system incorporating high quality Taiwanese linear guide rails and racks, together with Japanese servo drives, allowing speeds of up to 40 metres per minute to be achieved
- Integrated PC control system
- Automatic head focus system for automatically adjusting focal length
- Automatic capacitive height control system for optimal cutting
- Integrated red dot beam pointer for plate location/orientation and program dry run
- Superior fibre laser with up to 100,000 hours life span
- Integrated cutting table with removable slats and material recovery tray
- Optional Boxford supplied extraction system, which is IFA certified and meets the highest testing level (W3) facilitating the extraction of fumes from high alloy steels with over 30% chromium and nickel content





boxford

	BFL1390 1.0kw	BFL1390 1.5kw	BFL1390 2kw	BFL1390 3kw	
Cutting area (mm)		1300x900			
Z axis travel (mm)		100			
Laser power source	1.0kw	1.5kw	2kw	3kw	
Laser type	Fibre 1070nm WL				
Integrated laser cooling system	Water chiller				
Focus system	Auto Focus	Auto Focus	Auto Focus	Auto Focus	
Drive system		Servo motors			
Cutting thickness (mm)	12mm mild steel¹ 5mm stainless² 3mm mild steel³ 2mm stainless³ 3mm aluminium²	15mm mild steel ¹ 6mm stainless ² 4mm mild steel ³ 3mm stainless ³ 4mm aluminium ²	18mm mild steel ¹ 8mm stainless ² 4mm mild steel ³ 3mm stainless ³ 6mm aluminium ²	22mm mild steel ¹ 10mm stainless ² 4mm mild steel ³ 3mm stainless ³ 8mm aluminium ²	
Max cutting speed	40m/min				
Max acceleration	0.5G				
Location precision	<0.01				
Optics	<0.373mrad beam				
Machine weight	1500 kg				
Dimensions (w x d x h)	2350x2250x1900				
Mounting	Floor				
Safety	Class 2 closed configuration				
Operating modes	Cutting / Surface etching				
Compressed air	6.0 bar @ 420 l/min				
requirements			Low pressure compressed air cutting - 6.9 bar @ 650 l/min		
Optional extraction	High pressure compressed air cutting - 18 bar @ 1100 l/min				
Dimensions (w x d x h)	810mm x 940mm x 1350 mm				
Software	Cypcut				
Preferred file type	.dxf, .plt				
Power requirements	380V 3ph @ 32A				

¹ with oxygen gas

² with nitrogen gas ³ with 6 bar compressed air

Included as standard:

- · Class 1 laser safety enclosure with CE marked safety switches
- Auto-focus laser head
- Intergrated Windows OS computer
- Programming & nesting software
- Wireless operator keypad
- · Wireless keyboard and mouse
- · Pull out table to assist with sheet loading
- Motorised up/down door
- Chiller based laser source cooling system
- Full day on-site UK mainland training
- Warranty 2 years (excluding consumable items such as nozzles, lenses, protective glass, support slats and extraction filters)



Optional accessories:

- Bespoke downdraught fume extraction/ air filtration system
- Stand alone compressor for facilitating low pressure non-gas cutting and extraction
- · High pressure compressor for non-gas cutting of thick materials
- Additional cutting head consumables (cutting tips, lens protective glass, etc)
- Set of replacement filters for extraction/ air filtration system
- Pneumatic clamps for securing thin materials